

EPISTAR TRIDONIC



UVC LED Panel for Air Disinfection Code: LP525UVC



DRIVER

- Suitable for CE and ROHS Criterias
- High Efficiency >%90
- Harmonic Filter
- Lasts for 50.000 Hr



CABLE

- 0,80mm Thickness
- Electrolytic Solid Copper
- T1/PVC Isolation



Specification

Size	Light source	Driver	Voltage	Power	Wave Length	Ozone Production	Air Debit	Fan
595*595mm	UVC 3535 EPISTAR	TRIDONIC MEANWELL	220V-240V	25W	265- 280nm	No	58m3/h	Arctic
Material	Use	Tc=C°	Certificates	Application	Filter	Directive	Lifespan	Warranty
Metal PVC foam	Air Disinfection	-20/+45	ROHS/CE	INDOR	Without filter	LVD	15 000h	2 years

Use:

1. Inside Air Disinfection
2. Destroy bacteria, different type of fungi, viruses including different type of corona viruses
3. Install in ceiling for maximum efficiency
4. Use of special wave length 265-280nm has maximum bactericidal effect on viruses and has no Ozone production.
5. This wave length destroy Ozone molecules and turn back to Oxygen
6. You can disinfect when people and animals are present
7. This spectrum no change color and has no effect on rubber, plastic and other no living materials
8. Do not look directly in the panel air openings